

Product data sheet

Characteristics

HDS318B09M7P16M

Magnetic starter, HDS3-18, 0.16 A, 220/230 V, 50/60 Hz, metal



Main

Range of product	HDS3
Product or component type	Enclosed DOL starter
Device application	Motor control Motor protection
Device composition	HDC3 contactor HDR3s thermal overload relay
Thermal protection adjustment range	0.1...0.16 A
Motor power kW	50/60 Hz

Complementary

Housing material	Metal
Utilisation category	AC-3
[Uc] control circuit voltage	220/230 V AC 50/60 Hz
Control type	Push-button start green I Push-button stop/reset red O
Width	126 mm
Height	186 mm
Depth	146 mm

Environment

IP degree of protection	IP54
Standards	IEC 60947-4-1
Quality labels	CE
Ambient air temperature for operation	-5...40 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.