

## Product data sheet

### Characteristics

# HDS318B18M7M

Magnetic starter, HDS3-18, 18 A, 220/230 V, 50/60 Hz, metal



### Main

|                           |  |
|---------------------------|--|
| Range of product          | HDS3   |
| Product or component type | Enclosed DOL starter                           |
| Device application        | Motor control<br>Motor protection              |
| Device composition        | HDC3 contactor<br>HDR3s thermal overload relay |

### Complementary

|                              |   |
|------------------------------|---|
| Housing material             | Metal   |
| Utilisation category         | AC-3  |
| Protection type              | Without protection  |
| [Uc] control circuit voltage | 220/230 V AC 50/60 Hz                                     |
| Control type                 | Push-button start green I<br>Push-button stop/reset red O |
| Width                        | 126 mm  |
| Height                       | 186 mm  |
| Depth                        | 146 mm  |

### Environment

|                                       |               |
|---------------------------------------|---------------|
| IP degree of protection               | IP54          |
| Standards                             | IEC 60947-4-1 |
| Quality labels                        | CE            |
| Ambient air temperature for operation | -5...40 °C    |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.