

Product data sheet

HDW320M203FH5556H

Characteristics

Air circuit breaker, HDW3, 2000AF, 2000 A, 3P, fixed horizontal, 6 NO + 6 NC



Main

Range of product	HDW3
Product or component type	Air circuit breaker
Frame size	2000AF
[Icu] ultimate breaking capacity	50 kA at 690 V load 80 kA at 400 V load
[Ics] rated service breaking capacity	40 kA at 690 V 65 kA at 400 V
[Icw] rated short-time withstand current	40 kA at 690 V duration: 1 s 65 kA at 400 V duration: 1 s

Complementary

[In] rated current	2000 A
Poles description	3P
Mounting mode	Fixed
Mounting position	Horizontal
Voltage release type	Without motor mechanism, closing release, shunt release and undervoltage release
Maximum tripping time	25 ms
Maximum closing response time	70 ms
Auxiliary contact composition	6 NO + 6 NC
Product compatibility	Series intelligent controller iTR326H advance protection
Height	397 mm
Width	364 mm
Depth	327 mm
Net weight	41.4 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	41.4 kg
Package 1 Height	39.7 cm
Package 1 Width	36.4 cm
Package 1 Length	32.7 cm