

## Product data sheet

### Characteristics

# HLAY5BS442

Emergency stop pushbutton, HLAY5,  
mushroom Ø 30 mm, 1 NC, red



### Main

Range of product	HLAY5
Device presentation	Complete product
Product or component type	Emergency stop push-button
Mounting diameter	22 mm
Head type	Standard

### Complementary

Fixing collar material	Metal
Cap/operator or lens colour	Red
Shape of signaling unit head	Round
Reset	Turn to release
Operator profile	Red mushroom Ø 30 mm
Contacts type and composition	1 NC
Contact operation	Slow-break
Contacts usage	Standard contacts
Mechanical durability	100000 cycles
Connections - terminals	Screw clamp terminals
[I <sub>th</sub> ] conventional free air thermal current	6 A
[U <sub>imp</sub> ] rated impulse withstand voltage	6 kV
[I <sub>e</sub> ] rated operational current	2 A at 380 V 3.3 A at 220 V, AC-15 0.5 A at 220 V 1.1 A at 110 V, DC-13
Electrical durability	50000 cycles
E-commerce address	Hlay5-pushbuttons-mushroom-and-emergency-stop-pushbuttons-1

### Environment

Ambient air temperature for operation	-5...40 °C
IP degree of protection	IP40 IP65 with protective cover
Standards	IEC 60947-5-1