


### M11210



METRIC MALE 24° CONE SEAT HEAVY DUTY - DIN 20066 / ISO 12151-2  
 MACHO METRICO ASIENTO A 24° - SERIE PESADA DIN 20066 / ISO 12151-2  
 CES - DIN 20066 / ISO 12151-2  
 MASCHIO METRICO 24° - SERIE PESANTE DIN 20066 / ISO 12151-2

PART. REF.	HOSE BORE		THREAD	PIPE	DIMENSIONS mm					
	DN	inch			T	mm	B	A	C	Hi
M11210-04-16	6	1/4"	- 04	M 16x1,5	8	4,0	25,5	12,0		17
M11210-04-18	6	1/4"	- 04	M 18x1,5	10	6,0	26,5	12,0		19
M11210-04-20	6	1/4"	- 04	M 20x1,5	12	7,0	29,0	12,0		22
M11210-05-16	8	5/16"	- 05	M 16x1,5	8	5,5	26,0	12,0		17
M11210-05-18	8	5/16"	- 05	M 18x1,5	10	7,0	26,5	12,0		19
M11210-05-20	8	5/16"	- 05	M 20x1,5	12	7,0	29,0	12,0		22
M11210-06-18	10	3/8"	- 06	M 18x1,5	10	7,0	27,1	12,0		19
M11210-06-20	10	3/8"	- 06	M 20x1,5	12	7,0	29,1	12,0		22
M11210-06-22	10	3/8"	- 06	M 22x1,5	14	8,0	31,1	14,0		22
M11210-08-22	12	1/2"	- 08	M 22x1,5	14	9,3	31,5	14,0		22
M11210-08-24	12	1/2"	- 08	M 24x1,5	16	9,3	31,6	14,0		24
M11210-10-30	16	5/8"	- 10	M 30x2	20	15,0	35,7	16,0		30
M11210-10-36	16	5/8"	- 10	M 36x2	25	19,8	40,0	18,0		36
M11210-12-30	19	3/4"	- 12	M 30x2	20	15,0	37,0	16,0		30
M11210-12-36	19	3/4"	- 12	M 36x2	25	19,8	41,0	18,0		36
M11210-16-36	25	1"	- 16	M 36x2	25	19,8	42,3	18,0		36
M11210-16-42	25	1"	- 16	M 42x2	30	25,0	44,3	20,0		46
M11210-20-52	31	1.1/4"	- 20	M 52x2	38	30,0	50,5	22,0		55