



ZEC S.p.A.

Via Lungolorno 11 - 42052 Colorno (PR) - Italia Tel. 0521 816631 - Fax 0521 816772 info@zecspa.com - www.zecspa.com

Capitale sociale: Euro 1.000.000 C.F., P.IVA e n. Iscr. Reg. Imprese Parma: IT01720400348 Numero REA: PR - 173914

Conductive AS8 Series Thermoplastic hose - Oil proof Cover*

- PRESSURE FROM 245 TO 350 BAR SAFETY RATIO 1:4
- PRESSURE FROM 327 TO 467 BAR SAFETY RATIO 1:3
- SAE 100R8, ISO 3949 STANDARDS
- PATENT No. IT-1328746
- ELECTRICAL RESISTANCE LESS THAN 3 x $10^4 \,\Omega/m$





GENERAL INDUSTRY

TECHNICAL FEATURES

Metric

| | OID | | | OD | 1:4 WP | 1:3 WP | R MIN | g | |
|----------|-------|------|----|------|-----------|-----------|-------|-----|--------------|
| Code | inch | mm | DN | mm | bar | bar | mm | g/m | Ferrule Code |
| AS820102 | 3/16" | 4.8 | 5 | 10.0 | 350 | 467 | 35 | 88 | BP316R7 |
| AS830102 | 1/4" | 6.4 | 6 | 11.8 | 350 | 467 | 50 | 83 | BP14R7 |
| AS840102 | 5/16" | 8.0 | 8 | 14.3 | 325 | 433 | 60 | 122 | BP516R7V |
| AS850102 | 3/8" | 9.7 | 10 | 16.0 | 280 | 373 | 70 | 168 | BP38R7V |
| AS860102 | 1/2" | 13.0 | 12 | 20.3 | 245 | 327 | 95 | 218 | BP12R7V |

TECHNICAL FEATURES

Technical-constructive features:

Inner core in polyamide, reinforcement in due Aramid fiber braids, external covering in antiabrasion micro perforated polyurethane for the conduction of air and compatible gases. The hose's electrical resistance is less than 3 x $10^4 \Omega/m$ in accordance with ISO 8031 Standard.

Applications:

hoses of the AS8 Series have been created for the high pressure conduction of Polyols, Solvents, Paints, and compatible gases.

Working temperature:

from -40°C to +100°C from -40°F to +212°F.

Max. working temperature of air, water and water-based fluids is + 70°C (+158°F).

Working pressure:

Safety ratio 1:4 for DYNAMIC pressure (according to SAE norm) Safety ratio 1:3 for STATIC pressure

Vacuum rating:

1 of 2 4/2/2020, 11:18 AM 0.93 bar; 700 mm Hg

Specifications:

Hoses meet or exceed SAE J517 sect. SAE 100R8 - ISO 3949 Standards.

* Not provided for by SAE 100R8

Patent n° IT-1328746

*The oil-proof feature of the cover means that the hose is resistant to prolonged contact with oils and lubricants.



For any further information about the optional items, please contact the sales office (sales@zecspa.com)

2 of 2